

## CEVOL PRODUCT USER MANUAL FP.1 STILLAGE

### **STILLAGE DESCRIPTION**

FIXED POST STILLAGE.

SHEET BASE, FIXED POST, FULLY ENCLOSED MESH STILLAGE. LOCKABLE FRONT SWINGING GATE. PROVISIONS FOR ONE SHELF. SUITABLE FOR STORING IN PALLET RACKING.

**BASE DIMENSIONS:** 1152 X 1152mm **USABLE SPACE:** 1136 X 1136mm **OUTSIDE PALLET FEET:** 1167 X 1167mm OVERALL HEIGHT: 1025mm **INSIDE HEIGHT:** 910mm UNDER BASE: 100mm CUBIC CAPACITY: 1.2 M3 APPROXIMATE MASS PER UNIT: 125kg

#### **DESIGN SPECIFICATIONS**

RATED CAPACITY (N.A.T.A) CERTIFIED:

STACKING, FULLY LOADED:

FORKING FULLY LOADED:

1 HIGH, STATIC FLAT
1 HIGH FROM ANY SIDE

TRUCKING FULLY LOADED: 2 HIGH

### STILLAGE SAFETY ASSESSMENT

BEFORE USING ANY STILLAGE, THE OPERATOR MUST CHECK THAT:

- STACKING SPIGOTS ARE NOT BENT OR BROKEN.
- RACK RUNNERS ARE IN SAFE USABLE CONDITION.
- STILLAGE BASE IS IN GOOD CONDITION.
- POSTS ARE NOT DAMAGED AND THAT STILLAGE CAN BE STACKED OR STACKED ONTO.
- GATES CLOSE AND LOCK PROPERLY.

#### **STILLAGE DAMAGE & REPAIRS**

- DAMAGED STILLAGES SHOULD BE ASSESSED AND IF DEEMED TO BE UNSAFE, REMOVED FROM CIRCULATION.
- ANY TIME A STILLAGE IS REMOVED FROM CIRCULATION. IT SHOULD BE REPORTED TO THE RELEVANT SUPERVISOR.
- DAMAGED OR UNSAFE STILLAGES ARE TO BE RETURNED TO CEVOL INDUSTRIES FOR PROPER ASSESSMENT OR REPAIR.

#### **Disclaimer – Important Notice**

The information contained in this document is provided to assist you in the operation of the product described above. Cevol Industries Pty Ltd does not accept any liability howsoever arising from injury or damage howsoever caused (whether fatal or otherwise) arising out of the use of this product in any way whatsoever due to any negligent act, breach of duty, default or omission or both, on the part of Cevol Industries Pty Ltd its directors, employees or agents.



# **CEVOL PRODUCT USER MANUAL FP.1 STILLAGE**

#### GENERAL LOADING & TRUCKING OF STILLAGE

- ALWAYS EVENLY DISTRIBUTE THE LOADING OF PRODUCT INTO THE STILLAGE AS BEST AS POSSIBLE.
- WHEN STACKING STILLAGES. MAKE SURE THE STILLAGE HAS INTERLOCKED PROPERLY, BEFORE REMOVING THE FORK LIFT.
- AVOID HAVING HEAVY LOADS ON TOP OF THE STACK.

OPERATORS ARE NOT TO EXCEED ANY OF THE DESIGN SPECIFICATIONS LISTED ABOVE.

EACH STILLAGE HIRED OUT BY CEVOL INDUSTRIES IS IN A SAFE USABLE CONDITION, STENCILLED WITH THE MAXIMUM CAPACITY AND STACKING HEIGHT.

OPERATORS ARE TO REPORT ANY DAMAGED STILLAGE TO THEIR SUPERVISOR FOR ASSESSMENT OR RETURN TO CEVOL INDUSTRIES.

#### **Disclaimer – Important Notice**

The information contained in this document is provided to assist you in the operation of the product described above. Cevol Industries Pty Ltd does not accept any liability howsoever arising from injury or damage howsoever caused (whether fatal or otherwise) arising out of the use of this product in any way whatsoever due to any negligent act, breach of duty, default or omission or both, on the part of Cevol Industries Pty Ltd its directors, employees or agents.