



## **CEVOL PRODUCT USER MANUAL MM.1 STILLAGE**

### **STILLAGE DESCRIPTION**

BULK MESH STILLAGE.  
SHEET BASE, FIXED POST STILLAGE, MESH SIDES WITH HALF DROP FRONT MESH GATE.  
STACKABLE.

BASE DIMENSIONS:	1750 X 1061mm
USABLE SPACE:	1750 X 980mm
OUTSIDE PALLET FEET:	1840 X 1158mm
OVERALL HEIGHT:	1285mm
INSIDE HEIGHT:	1070mm
UNDER BASE:	100mm
CUBIC CAPACITY:	2.0 M3
APPROXIMATE MASS PER UNIT:	174kg

### **DESIGN SPECIFICATIONS**

RATED CAPACITY (N.A.T.A) CERTIFIED:	NET 1000kg PER UNIT
STACKING, FULLY LOADED:	4 HIGH, STATIC FLAT
FORKING FULLY LOADED:	1 HIGH FROM ANY SIDE
TRUCKING FULLY LOADED:	2 HIGH

### **GATES OPERATION**

#### **TO OPEN:**

HOLD ON TO THE TOP OF THE GATE AND LIFT ALL THE WAY TO ITS UPWARD LIMIT. SWING GATE OUTWARD AND DOWN INTO OPEN POSITION.

#### **TO CLOSE:**

SWING GATE UPWARD AND LOCATE INTO TOP GATE CATCHES.

### **STILLAGE SAFETY ASSESSMENT**

BEFORE USING ANY STILLAGE, THE OPERATOR MUST CHECK THAT:

- PALLET FEET ARE NOT BENT OR BROKEN.
- GATE FULLY LOCATES INTO CATCHES.
- RACK RUNNERS ARE IN SAFE USABLE CONDITION.
- STILLAGE BASE IS IN GOOD CONDITION.
- POSTS ARE NOT DAMAGED AND THAT STILLAGE CAN BE STACKED OR STACKED ONTO.

#### **Disclaimer – Important Notice**

The information contained in this document is provided to assist you in the operation of the product described above. Cevol Industries Pty Ltd does not accept any liability howsoever arising from injury or damage howsoever caused (whether fatal or otherwise) arising out of the use of this product in any way whatsoever due to any negligent act, breach of duty, default or omission or both, on the part of Cevol Industries Pty Ltd its directors, employees or agents.



## **CEVOL PRODUCT USER MANUAL MM.1 STILLAGE**

### **STILLAGE DAMAGE & REPAIRS**

- DAMAGED STILLAGES SHOULD BE ASSESSED AND IF DEEMED TO BE UNSAFE, REMOVED FROM CIRCULATION.
- ANY TIME A STILLAGE IS REMOVED FROM CIRCULATION. IT SHOULD BE REPORTED TO THE RELEVANT SUPERVISOR.
- DAMAGED OR UNSAFE STILLAGES ARE TO BE RETURNED TO CEVOL INDUSTRIES FOR PROPER ASSESSMENT OR REPAIR.

### **GENERAL LOADING & TRUCKING OF STILLAGE**

- ALWAYS EVENLY DISTRIBUTE THE LOADING OF PRODUCT INTO THE STILLAGE AS BEST AS POSSIBLE.
- WHEN STACKING STILLAGES. MAKE SURE THE STILLAGE HAS INTERLOCKED PROPERLY, BEFORE REMOVING THE FORK LIFT.
- AVOID HAVING HEAVY LOADS ON TOP OF THE STACK.

OPERATORS ARE NOT TO EXCEED ANY OF THE DESIGN SPECIFICATIONS LISTED ABOVE.

EACH STILLAGE HIRED OUT BY CEVOL INDUSTRIES IS IN A SAFE USABLE CONDITION, STENCILLED WITH THE MAXIMUM CAPACITY AND STACKING HEIGHT.

OPERATORS ARE TO REPORT ANY DAMAGED STILLAGE TO THEIR SUPERVISOR FOR ASSESSMENT OR RETURN TO CEVOL INDUSTRIES.

### **Disclaimer – Important Notice**

The information contained in this document is provided to assist you in the operation of the product described above. Cevol Industries Pty Ltd does not accept any liability howsoever arising from injury or damage howsoever caused (whether fatal or otherwise) arising out of the use of this product in any way whatsoever due to any negligent act, breach of duty, default or omission or both, on the part of Cevol Industries Pty Ltd its directors, employees or agents.