



## **CEVOL PRODUCT USER MANUAL D STILLAGE**

### **STILLAGE DESCRIPTION**

FIXED POST STILLAGE.

SHEET BASE, FIXED POST STILLAGE. ONE DROPPER EACH END. OPEN FRONT AND REAR.

BASE DIMENSIONS:	1232 X 927mm
USABLE SPACE:	1152 X 927mm
OUTSIDE PALLET FEET:	1325 X 1020mm
OVERALL HEIGHT:	1254mm
INSIDE HEIGHT:	1060mm
UNDER BASE:	100mm
CUBIC CAPACITY:	1.13 M3
APPROXIMATE MASS PER UNIT:	57kg

### **DESIGN SPECIFICATIONS**

RATED CAPACITY (N.A.T.A) CERTIFIED:	NET 500kg PER UNIT
STACKING, FULLY LOADED:	4 HIGH, STATIC FLAT
FORKING FULLY LOADED:	1 HIGH FROM ANY SIDE
TRUCKING FULLY LOADED:	2 HIGH

### **STILLAGE SAFETY ASSESSMENT**

BEFORE USING ANY STILLAGE, THE OPERATOR MUST CHECK THAT:

- PALLET FEET ARE NOT BENT OR BROKEN.
- STILLAGE BASE IS IN GOOD CONDITION.
- POSTS ARE NOT DAMAGED AND THAT STILLAGE CAN BE STACKED OR STACKED ONTO.

### **STILLAGE DAMAGE & REPAIRS**

- DAMAGED STILLAGES SHOULD BE ASSESSED AND IF DEEMED TO BE UNSAFE, REMOVED FROM CIRCULATION.
- ANY TIME A STILLAGE IS REMOVED FROM CIRCULATION. IT SHOULD BE REPORTED TO THE RELEVANT SUPERVISOR.
- DAMAGED OR UNSAFE STILLAGES ARE TO BE RETURNED TO CEVOL INDUSTRIES FOR PROPER ASSESSMENT OR REPAIR.

### **Disclaimer – Important Notice**

The information contained in this document is provided to assist you in the operation of the product described above. Cevol Industries Pty Ltd does not accept any liability howsoever arising from injury or damage howsoever caused (whether fatal or otherwise) arising out of the use of this product in any way whatsoever due to any negligent act, breach of duty, default or omission or both, on the part of Cevol Industries Pty Ltd its directors, employees or agents.



## **CEVOL PRODUCT USER MANUAL D STILLAGE**

### **GENERAL LOADING & TRUCKING OF STILLAGE**

- ALWAYS EVENLY DISTRIBUTE THE LOADING OF PRODUCT INTO THE STILLAGE AS BEST AS POSSIBLE.
- WHEN STACKING STILLAGES. MAKE SURE THE STILLAGE HAS INTERLOCKED PROPERLY, BEFORE REMOVING THE FORK LIFT.
- AVOID HAVING HEAVY LOADS ON TOP OF THE STACK.
- OPEN FRONTED STILLAGE. RECOMMEND SECURING PRODUCT TO STILLAGE BEFORE TRANSPORTING.
- PALLET HAS NO FORK TYNE GUIDES AND CAN SLIDE AROUND ON FORK LIFT.

OPERATORS ARE NOT TO EXCEED ANY OF THE DESIGN SPECIFICATIONS LISTED ABOVE.

EACH STILLAGE HIRED OUT BY CEVOL INDUSTRIES IS IN A SAFE USABLE CONDITION, STENCILLED WITH THE MAXIMUM CAPACITY AND STACKING HEIGHT.

OPERATORS ARE TO REPORT ANY DAMAGED STILLAGE TO THEIR SUPERVISOR FOR ASSESSMENT OR RETURN TO CEVOL INDUSTRIES.

### **Disclaimer – Important Notice**

The information contained in this document is provided to assist you in the operation of the product described above. Cevol Industries Pty Ltd does not accept any liability howsoever arising from injury or damage howsoever caused (whether fatal or otherwise) arising out of the use of this product in any way whatsoever due to any negligent act, breach of duty, default or omission or both, on the part of Cevol Industries Pty Ltd its directors, employees or agents.